

VESSEL SAFETY CHECK DECAL REQUIREMENTS	YES	NO	N/A												
<p>1. DISPLAY OF NUMBERS - Must be permanently attached to each side of the forward half of the boat. Proper spacing, a space or hyphen must separate the letters from the numbers, contrasting color, minimum 3" block letters. Place State validation sticker 3" aft of numbers (e.g. NJ 1234 AB or NJ-1234-AB)</p>															
<p>2. REGISTRATION/DOCUMENTATION - Must be on board, vessel must be registered with state of usage.</p> <p>If Documented Vessel: Documentation numbers must be permanently marked on a visible part of the interior structure. The documented boat's name and hailing port must be displayed on the exterior hull in letters not less than 4" in height.</p>															
<p>3. PERSONAL FLOTATION DEVICE (Life Jackets) - Acceptable PFDs must be U.S. Coast Guard approved and in good serviceable condition. A wearable PFD of suitable size is required for each person on the boat. Children must have properly fitted PFDs designed for children. Children 12 years or younger must be wearing their PFD at all times while on the boat. Wearable PFDs shall be "readily accessible." Boats 16 feet or longer, must also have one Type IV (throwable) device, which shall be "immediately available." PFDs shall NOT be store in unopened plastic packaging. For Personal Watercraft riders, the PFD must be worn. An impact rating is recommended, but not required.</p>															
<p>4. VISUAL DISTRESS SIGNALS - Recreational boats 16 feet and over, used on coastal waters or the Great Lakes are required to carry a minimum of either (1) 3 day and 3 night pyrotechnic devices (like flares), (2) one day non-pyrotechnic device (flag) and one night non-pyrotechnic device (auto SOS light) or (3) a combination of (1) and (2). Recreational boats less than 16 feet on coastal waters or the Great Lakes need only carry night visual distress signals when operating from sunset to sunrise.</p>															
<p>5. FIRE EXTINGUISHER - Fire extinguishers are required if one of the following conditions exists: (1) inboard engine(s); (2) Double bottom hulls not completely sealed or not completely filled with flotation materials (3) Closed living space (4) Closed stowage compartments that contain flammable materials or (5) Permanently installed fuel tanks. Recreational boats less than 26 feet and propelled by outboard motors are NOT required to have fire extinguishers unless one or more of the conditions (2-5) listed above applies. NOTE: Fire extinguishers must be readily accessible and verified as serviceable.</p> <p>Owners of recreational vessels produced after December 2017 are required to carry fire extinguishers labeled 5-B, 10-B, or 20-B. Those labeled B-I and B-II are no longer acceptable.</p> <table border="1" data-bbox="142 1665 1128 1833"> <thead> <tr> <th>Boat Length</th> <th>No Fixed System</th> <th>With Fixed System</th> </tr> </thead> <tbody> <tr> <td>L < 26 Ft.</td> <td>One (5-B or 10-B)</td> <td>0</td> </tr> <tr> <td>26' < L < 40'</td> <td>Two (5-B or 10-B) or One 20-B</td> <td>One (5-B or 10-B)</td> </tr> <tr> <td>40' < L < 65'</td> <td>Three (5-B or 10-B) or One 20-B and One (5-B or 10-B)</td> <td>Two (5-B or 10-B) or One 20-B</td> </tr> </tbody> </table>	Boat Length	No Fixed System	With Fixed System	L < 26 Ft.	One (5-B or 10-B)	0	26' < L < 40'	Two (5-B or 10-B) or One 20-B	One (5-B or 10-B)	40' < L < 65'	Three (5-B or 10-B) or One 20-B and One (5-B or 10-B)	Two (5-B or 10-B) or One 20-B			
Boat Length	No Fixed System	With Fixed System													
L < 26 Ft.	One (5-B or 10-B)	0													
26' < L < 40'	Two (5-B or 10-B) or One 20-B	One (5-B or 10-B)													
40' < L < 65'	Three (5-B or 10-B) or One 20-B and One (5-B or 10-B)	Two (5-B or 10-B) or One 20-B													

For recreational vessels **produced before 2018**, B-I and B-II are still acceptable, while serviceable until they reach expiration date. December 31 twelve (12) years from "date of manufacture".

Boat Length	No Fixed System	With Fixed System
L < 26 Ft.	One B-I	0
26' < L < 40'	Two B-I or One B-II	One B-I
40' < L < 65'	Three B-I or one B-I & one B-II	Two B-I or one B-II

"Non-Rechargeable" fire extinguishers "expire" on December 31 twelve (12) years from "date of manufacture". After "expired" does NOT count towards required number of extinguishers.

"Rechargeable" fire extinguishers require "annual" maintenance [inspection].

- The annual "Tag or Label"
 - Has month & year that maintenance was done.
 - Has [NFPA] technician's certification identifier.
 - Re-starts the "annual" limit.

"Rechargeable" fire extinguishers, if not inspected by [NFPA] technician, "expire" on December 31 twelve (12) years from "date of manufacture". After "expired" does NOT count towards required number of extinguishers.

6. VENTILATION - Boats with gasoline engines in closed compartments, built after 1 August 1980 must have a powered ventilation system. Those built prior to that date must have natural or powered ventilation. Boats with closed fuel tank compartments built after 1 August 1978 must meet requirements by displaying a "certificate of compliance." Boats built before that date must have either natural or powered ventilation in the fuel tank compartment.

7. BACKFIRE FLAME ARRESTER - All gasoline powered inboard/outboard or inboard motorboats must be equipped with an approved backfire flame control device. (Approved by UL-1111 or SAE-1928, tight, clean)

8. SOUND PRODUCING DEVICE - To comply with Navigation Rules and for distress signaling purposes all boats must carry a sound producing device (Horn, whistle, siren, or other device) capable of a 4-second blast audible for 1/2 mile. Boats larger than 39.4 ft. are also required to have a bell.

9. NAVIGATION LIGHTS - All boats must be able to display navigation lights between sunset and sunrise and in conditions of reduced visibility. Boats 16 feet or more in length must have properly installed, working navigation lights and an all-around anchor light capable of being lit independently from the red/green/white "running" lights. (Must operate and show proper configuration)

10. POLLUTION PLACARD - Boats 26 ft and over with machinery compartment must display an oily waste "pollution" placard.

<p>11. MARPOL TRASH PLACARD - Boats 26 ft & over in length, operating in U.S. navigable waters, must display a "Marpol" trash placard. Oceangoing boats 40 feet and overs must also have a written trash disposal plan available onboard.</p>			
<p>12. MARINE SANITATION DEVICE - Any installed toilet must be a Coast Guard approved device. Overboard discharge outlets must be capable of being sealed.</p>			
<p>13. NAVIGATION RULES - Boats 39.4 ft. and over must have on board a current copy of the Navigation Rules.</p>			
<p>14. STATE REQUIREMENTS - These requirements must be met before the "Vessel Safety Check" decal can be awarded. A boat must meet the requirements of the state in which it is being examined.</p> <p>In Florida, passengers 6 years of age and under are required to wear a Coast Guard-approved, Type I, II or III life jacket while on board any boat that is under 26 feet in length, while the boat is underway. If the boat is anchored, moored, made fast to the shore, or aground, then it is not considered the be 'underway'.</p> <p>A noise muffling device is required in Florida. Enforcement authorities can request that a boat owner submit to a sound level test.. The exhaust of every engine used on an airboat in the state of Florida must be muffled with one of the following: An automotive type factory muffler. An underwater exhaust. Another device that is capable of muffling the sound of the engine exhaust.</p>			
<p>15. OVERALL VESSEL CONDITION - As it applies to this Vessel. Including, but not limited to:</p> <p>a. Deck free of hazards and clean bilge - The boat must be free from fire hazards, in good overall condition, with bilges reasonably clean and visible hull structure generally sound. The use of automobile parts on boat engines is not acceptable (Alternators, distributors, starters, generators, accessory motors, starter solenoids, carburetors, fuel pumps). The engine horsepower must not exceed that shown in the capacity plate. Boat shall not be overloaded, and not overpowered.</p> <p>b. Electrical and Fuel Systems: The electrical system must be protected by fuses or manual reset circuit breakers. Switches and fuse panels must be protected from rain or water spray. Wiring must be in good condition, properly installed and with no exposed areas of deteriorated insulation. Batteries must be secured and terminals covered to prevent accidental arcing. If installed, self-circling or kill switch mechanism must be in proper working order. All PWCs require an operating self-circling or kill switch mechanism.</p> <p>c. Fuel Systems - Portable fuel tanks (normally 7 gallons capacity or less) must be constructed of non-breakable material and free of corrosion and leaks. All vents must be capable of being closed. The tank must be secured and have a vapor-tight, leak-proof cap. Each permanent fuel tank must be properly ventilated. Tanks must be grounded/vented. Hoses must be in good condition, no leaks.</p> <p>d. Galley/Heating Systems - System and fuel tanks must be properly secured with no flammable materials nearby.</p> <p>e. Engine Cutoff Switch - Owners of recreational vessels (less than 26 feet in length, with an engine capable of 115 lbs. of static thrust; 3 HP or more) produced after December 2019 are required to maintain the ECOS system on their vessel in</p>			

<p>a serviceable condition. Also applies to older recreational vessels (less than 26 feet in length) with an installed ECOS system. Using the ECOS-Link (ECOSL) is required when the primary helm is not within an enclosed cabin, and when the boat is operating on plane or above displacement speed.</p>			
<p>RECOMMENDED ITEMS</p>			
<p>I. MARINE RADIO</p>			
<p>II. DEWATERING DEVICE - pumps must work, extra manual bailer (bucket, can, scoop, hand operated pump)</p>			
<p>III. MOUNTED FIRE EXTINGUISHER</p>			
<p>IV. ANCHOR & ANCHOR LINE - Suitable for the boat & the area. Line must be 5 to 7 times the depth of the water in the area to be anchored.</p>			
<p>V. FIRST AID & PERSON IN THE WATER (PIW) KIT - PIW consists of one extra wearable PFD and a throwable type IV PFD with a line.</p>			
<p>VI. INLAND VISUAL DISTRESS SIGNALS</p>			
<p>VII. CAPACITY/CERTIFICATE OF COMPLIANCE LABEL - Visible, Monohull power boats under 20 ft., all boats with installed engines, except outboards, manufactured after 10/31/72.</p>			